

PA-LNB162L-C17UL.4.1.R001



Dimensions

Length	38mm
Width	19mm
Height	136mm



IEC62133-2:2017



MH45979 4)

*picture only for reference

Data for Pack

Nominal voltage	7.2V	5V - 8.2V (usable voltage range)		
Nominal capacity	6.7Ah	typ. @ 4,2V/cell @4,1V/cell capacity reduction of appr. 12%		
Used cell in pack	4pcs	18650		
Internal resistance pack	84mΩ	±10% typical value @20°C with fresh cells		
Charge voltage	8.2V	max ²⁾		
Charge current	low temp	2.4A 0°C < T < 10°C ³⁾		
	standard	3A 10°C < T < 45°C ³⁾		
Discharge	standard	3A -20°C < T < 60°C ^{1) 3)}		
	max cont.	5A -20°C < T < 60°C ^{1) 3)}		
Over Voltage Cut-off (per cell)	4.1V	typical @Ta 25°C 'safety unit cut-off		
Over Voltage release (per cell)	4V	typical @Ta 25°C		
Under Voltage Cut-off (per cell)	2.4V	typical @Ta 25°C; recovery = charger connect		
Discharge current protection	>6.67A	typical @Ta 25°C; recovery = load remove		
Charge current protection	>5A	typical @Ta 25°C; recovery = charger remove		
load short circuit protection	>54A	typical @Ta 25°C; max 300μs		
non resettable current fuse	7A			
non resettable second over voltage cut-off	4.35V			
Connector	Molex	Microfit 3.0 43645-0300	Pin1	Bat+
			Pin2	NTC
			Pin3	GND
Cable Length	144mm	± 5mm		
Weight	195g	± 5g		
Watt-hour rating	48Wh	acc. to UN38.3 TSR		

Charging method

CC/CV Charger with NTC temperature control; max. charge voltage shall be limited to 4,1V

- 1) below 0°C with limited performance data (current output and available capacity)
- 2) Recommended Charge Voltage in standby applications / UPS = 4,0V; Do not apply continous charge (trickle charge) method
- 3) Cell surface temperature
- 4) UL conditions of acceptability to be consider in end application